

DR-Series

Wires specification: EN2267-010



General purpose high-performance hook-up wires.
Designed for aerospace and other applications
requiring excellent thermal stability and light weight.



Cable characteristics



-65 +260°C



Excellent



FAR25_
ABD0031

Environmental

- Operating temperature: -65°C to 260°C (ambient temperature + current heating)
- Resistant to: Aircraft fluids (oils, hydrocarbons, kerosene, skydrols...), Chemical agents
- Arc Tracking resistant

Electrical

Maximum operating voltage:

- 115V (phase to neutral) or 200V (phase to phase) AC Electrical systems of aircraft
- 230/400V AC in pressurized zones with specific installation rules to take account of possible short circuit effects.

Operating frequency: up to 2000Hz

Cable design



3



2



1

1. Conductor:
AWG 26 and AWG 24: Nickel plated copper alloy
AWG 22 to AWG 2: Nickel plated copper
2. Reinforce Polyimide tape
3. PTFE tape, UV-laser sensitive

Identification

- Standard versions are based on PTFE tape that can be marked by UV-Laser
- Color of Insulation: AWG 26: Light Yellow
AWG 22: Light Green
Other Gauges: White

Marking (example)

EN DR yy FR A zz
1 2 3 4 5

e.g. EN DR 24 FR A 23

1. Short Designation
2. Gauge
3. Country of Origin
4. Manufacturer (A: Draka)
5. Manufacturing Year

Specifications

Conductors

- For AWG 26 to AWG 6 according to EN 4434 table 2: tight tolerance
- For AWG 4 and AWG 2: EN 2083

Wires Specifications

EN2267-010 for marking by UV-Laser Markers

Technical Specification

EN2084

Compliant to ABD0031

Flammability, Smoke and Toxicity requirements and 14 CFR FAR25-1713

Dimensional

Short designation	EN reference	Nominal cross section	AWC*	Linear resistance max. at 20°C		Outer diameter				Weight max.	
		mm²		Ω/km	Ω/1000ft	min.		max.			
						mm	inch	mm	inch	kg/km	Lbs/1000ft
DR26	EN2267-010A001S	0.15	26	160.0	48.77	0.75	0.0295	0.84	0.0331	2.08	1.397
DR24	EN2267-010A002S	0.25	24	114.0	34.75	0.85	0.0335	0.96	0.0378	2.72	1.827
DR22	EN2267-010A004S	0.40	22	60.0	18.29	1.00	0.0394	1.10	0.0433	4.14	2.781
DR20	EN2267-010A006S	0.60	20	33.2	10.12	1.22	0.0480	1.34	0.0528	6.85	4.604
DR18	EN2267-010A010S	1	18	21.1	6.43	1.46	0.0575	1.61	0.0634	10.43	7.008
DR16	EN2267-010A012S	1.2	16	14.5	4.42	1.76	0.0693	1.92	0.0756	14.61	9.817
DR14	EN2267-010A020S	2	14	10.9	3.32	2.04	0.0803	2.24	0.0882	19.78	13.291
DR12	EN2267-010A030S	3	12	6.8	2.07	2.50	0.0984	2.70	0.1063	31.33	21.060
DR10	EN2267-010A051S	5	10	4.1	1.25	3.13	0.1232	3.33	0.1311	49.85	33.497
DR8	EN2267-010A090S	9	8	2.3	0.70	4.10	0.1614	4.40	0.1732	90.00	60.490
DR6	EN2267-010A140S	14	6	1.58	0.48	5.30	0.2087	5.70	0.2244	135.00	90.728
DR4	EN2267-010A220S	22	4	0.97	0.30	6.71	0.2642	7.41	0.2917	222.00	149.206
DR2	EN2267-010A340S	34	2	0.61	0.19	8.28	0.326	9.16	0.3606	347.00	233.212

*Closest American Wire Gauge

Bending radius

Permissible bend radius (recommendation following EN3197)	AWG		
	26 to 10	8 to 4	2
Static use	6xØ	8xØ	11xØ
Dynamic use	12xØ	16xØ	22xØ



Prysmian câbles et systèmes France
Head Office

23 avenue Aristide Briand - BP 801 - PARON - 89108 SENS Cedex / France
Tel : +33 (0)4 72 46 73 99 - infocables.fr@prysmian.com

Draka Fileca SAS

D 1001 - 60730 Sainte-Geneviève / France
fileca-office@prysmian.com



www.prysmian.com



© PRYSMIAN 2024

All Rights Reserved. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian. The information is believed correct at the time of issue. Prysmian reserves the right to amend this specification without notice. This specification is not contractually valid unless specifically authorised by Prysmian.